



F<u>eatures</u>

- It has got TCP/IP communication for reliable network system.
- It is backed by advance access control functions.
- Can be integrated easily with existing security systems.
- It supports built-in web server.
- The controller supports different Wiegand formats.
- It includes ID card reader and MF card reader.

ACCESS CONTROL SYSTEM

Model - NS-AC-001/002/004

Overview

Access Control System is a security solution that regulates entry to physical spaces. It restricts unauthorized access, enhances security, improves safety, streamlines operations, allows customized access levels, and offers scalability for evolving security needs.

It is a robust and rugged system designed to enhance security of the premises.

B<u>enefits</u>

- Streamline access management processes and reduce administrative burdens
- Mitigate risks and prevent potential security incidents.
- Restrict unauthorized access and protect valuable assets.
- Maintain records for accountability and investigation purposes.
- Grant specific permissions based on individual roles.
- Easily expand or modify the system to meet changing needs.

Technical Specifications

| Model | NS-AC-001 | NS-AC-002 | NS-AC-004 |
|--|--|--|--|
| CPU | Arm Architecture | Arm Architecture | Arm Architecture |
| Communication | TCP/IP 10M/100M adaptive | TCP/IP 10M/100M adaptive | TCP/IP 10M/100M adaptive |
| Card/user Capacity | 20,000 Users | 20,000 Users | 20,000 Users |
| Log Event Buffers(offline) | 100,000 event buffers | 100,000 event buffers | 100,000 event buffers |
| Number of Readers | 2 readers (Weigand) | 4 readers (Weigand) | 4 readers (Weigand) |
| Door Controlled | 1 door | 2 doors | 4 doors |
| Input | 1 door sensor and 1 exit device | 2 door sensor and 2 exit devices | 4 door sensor and 4 exit devices |
| Output | 1 Relay output | 2 Relay output | 4 Relay output |
| Door opening time | 1-600 seconds (adjustable) | 1-600 seconds (adjustable) | 1-600 seconds (adjustable) |
| Power interruption protection measure | High Speed Memory, Records never lose | High Speed Memory, Records never lose | High Speed Memory, Records never lose |
| Door open alarm | Yes | Yes | Yes |
| Alarm linkage | Software linkage | Software linkage | Software linkage |
| Remote Door Open | Yes | Yes | Yes |
| Door Inter lock | Yes | Yes | Yes |
| Anti-pass back and tail | Yes | Yes | Yes |
| Multi-card Door Open | Yes | Yes | Yes |
| Electronic map | Yes | Yes | Yes |
| First card unlocking | Yes | Yes | Yes |
| Unlock based on internal and external validation | Yes | Yes | Yes |
| Keypad (card + password, super password) | Yes | Yes | Yes |
| Package included: | Controller, software, manual. | Controller, software, manual. | Controller, software, manual. |
| Operation Temperature | -40 °C~70 °C | -40°C~70 °C | -40°C~70 °C |
| Operation Humidity | 10-90 % RH , No Condensation | 10-90 % RH , No Condensation | 10-90 % RH , No Condensation |



Disclaimer:

Brief product specifications are mentioned, that may change without prior notice, please check with OEM before purchase. Images are shown for reference only; the actual product may differ due to product enhancement.