



# Auto Pneumatic Bollard



# Auto Pneumatic Bollard

NS-APBS10-168-600-5

NS-APBS10-220-600-6

NS-APBS10-220-900-6



## Features

- » Pneumatic driven bollard
- » 100% duty cycle for high frequency use
- » Fast lower-raise operation
- » Environmentally friendly system
- » High visibility gloss and reflective
- » Emergency operation

Item No.	NS-APBS10-168-600-5	NS-APBS10-220-600-6	NS-APBS10-220-900-6
Diameter	168mm	220mm	275mm
Blocking Height	600mm	900mm	900mm
Cylinder Thickness	5mm	6mm	6mm
Cylinder material	Carbon steel / 304SS / 316SS		
Bollard pit material	Carbon steel		
Voltage	220V 50Hz		
Surface treatment	Carbon steel: Galvanization and powder coated (color can be customized according to RAL No.) Stainless steel: Hairline polish		
Rising speed	30cm/S		
Lowing speed	20cm/S		
IP Level	IP 67		
Working temperature	-40℃ — +70℃		
Frequency use	High intensive		
Reflective tape	One 3M diamond series reflective, customized logo is available		
LED light	Red LED light		
Accessories	Remote controller×2		
Optional	Push button, loop detector, photocell, buzzer, traffic light, heater can be optional		



Disclaimer: Brief product specifications are mentioned, that may change without prior notice, please check with OEM before purchase. Images are shown for reference only; the actual product may differ due to product enhancement.