



PARKING



Novus

BOOM BARRIER



BOOM BARRIER NS-BS11-V60D

Boom barrier offers robust security solutions with its compact design and sturdy construction. Operating on a stable 220VDC supply, it can work efficiently in diverse weather conditions. The 150W motor enables quick lifting, while its adaptability to $\leq 85\%$ humidity and a remote range of 30m enhance its efficiency. It is easy to install and operate.



scan to visit website

Features

- ▶ Build with a 1.8mm thickness for longevity.
- ▶ Operates with power supply of 220VDC.
- ▶ working temperature ranging from -40°C-85°C.
- ▶ 150W motor with lifting speed from 1 to 6s.
- ▶ Can function from distance up to 30 meters.
- ▶ Versatile design with telescopic arm options of 4-6m.

Benefits

- ▶ Reliable barrier for controlled access points.
- ▶ Compact design suits varied locations.
- ▶ Restricts unauthorized access effectively.
- ▶ Functions reliably in diverse weather conditions.
- ▶ Rapid barrier operation aids traffic flow.
- ▶ Easy management from a distance.

Technical Specifications

Arm Optional	Telescopic Arm 4-6m 2pcs remote control Include 6m Arm
Traffic Indication	yes

Technical Specifications

Opening / Closing	1.5 to 6 Sec
Housing Size (In mm)	320*245*985 (W*D*H)
Thickness	1.8 MM
Working Power Supply	220VDC+10%
Working Temperature	40°C 85°C
Motor Power	150 W
Lifting speed	1-6S
IP Rating	IP 54
Relative Humidity	≤85% No Condensation
Remote Control Distance	≥ 30 Meter
Color	Grey/Red/Black
Weight	45 KG
MCBF	5 Million

image showing the motor, card and other fitted items inside.



Disclaimer: Brief product specifications are mentioned, that may change without prior notice, please check with OEM before purchase. Images are shown for reference only; the actual product may differ due to product enhancement.