



# Electro-Hydraulic Bollard



# Electro-Hydraulic Bollard

NS-EHBS10-168-600-5

NS-EHBS10-220-900-6



## Features

- » Motor and hydraulic cylinder integration
- » Intensive use
- » Easy to install and operate
- » Low maintenance cost
- » Anti-rust treatment
- » High visibility gloss and reflective
- » Emergency operation

Item No.	NS-EHBS10-168-600-5	NS-EHBS10-220-900-6
Diameter	168mm	220mm
Blocking Height	600mm	900mm
Cylinder Thickness	5mm	6mm
Cylinder material	Carbon steel / 304SS / 316SS	
Bollard pit material	Carbon steel	
Voltage	220V 50Hz	
Surface treatment	Carbon steel: Galvanization and powder coated (color can be customized according to RAL No.) Stainless steel: Hairline polish	
Rising speed	30cm/S	
Lowing speed	20cm/S	
IP Level	IP 67	
Working temperature	-40℃ — +70℃	
Frequency use	High intensive	
Impact resistance	550Kj	
Reflective tape	One 3M diamond series reflective, customized logo is available	
LED light	Red LED light	
Accessories	Remote controller×2	
Optional	Push button, loop detector, photocell, buzzer, traffic light, heater can be optional	



Disclaimer: Brief product specifications are mentioned, that may change without prior notice, please check with OEM before purchase. Images are shown for reference only; the actual product may differ due to product enhancement.