



SWING BARRIER

Entrance Management System

Model : NS-SS9-V120



Swing Barrier NS-SS9-V120

Overview



Swing barrier is an entrance control device widely used in pedestrian entry management. The device features a swing barrier that allows and restricts entry of a person based on authentication criteria. Widely used in various settings such as transportation hubs and office buildings, Swing barrier offer a balance between security and user-friendly access.



Features

- ▶ Generous 600mm passage for easy access.
- ▶ Robust SUS 304 stainless steel construction.
- ▶ Swift response time of 0.2 seconds.
- ▶ Acoustic alarm, LED indication, infrared detectors.
- ▶ Reliable DC24V motor, supercapacitor backup (12V/3A).
- ▶ Sturdy construction with enhanced efficiency.

Benefits

- ▶ Robust barrier prevents unauthorized access.
- ▶ Compact design maximizes available area.
- ▶ Wide passage ensures comfortable and easy entry.
- ▶ Offers both single and bi-directional access options.
- ▶ Intuitive design for hassle-free operation by users
- ▶ Equipped with alarms and detectors for enhanced security.

Technical Specifications

Product Size	1200*185*980mm
Material	SUS 304 stainless steel
Material Thickness	1.2mm+1.0mm
Pass Width	600mm
Passage Direction	Single directional / Bi-directional
Throughput Rate	25~30p/m
Reaction Time	0.2S
Acoustic Alarm	Buzzer Alarm
LED	Triple Color LED
Driving Voltage	DC24V 6.25A
Power Input	AC 110~220V±10%
Working Temperature	-20~+70 C
Sensor	4 pairs of active infrared intrusion detector
Motor	Brushless DC Motor
Mechanism	Brushless Anti-collision Integrated Mechanism
Back up power	Supercapacitor (12V/3A)
Indication	LED direction indication
Weight	≤ 60 kg
IP Rating	44
MCBF	6 + Million
Tourque motor	Higher



Disclaimer: Brief product specifications are mentioned, that may change without prior notice, please check with OEM before purchase. Images are shown for reference only; the actual product may differ due to product enhancement.