

SEMI-AUTOMATIC TURNSTILE GATE

Entrance Management System

Model -NS-TSI-V22D0

Overview

Semi-automatic turnstile gate is a type of access control system that consists of rotating arms that allow or restrict access to a secured area. It is operated manually by the user pushing the arms to gain access.

The gate is commonly used in public transportation systems and amusement parks, and buildings to regulate access.

Features

- Operated by users pushing the arms to gain access.
- Made of sturdy materials to withstand heavy usage.
- Prevents multiple people from entering with a single authorization.
- Settings can be adjusted for customized security levels.
- Compatible with various access control systems.
- Does not degrade or deform owing to its sturdy construction .

Benefits

- Affordable option compared to fully automatic turnstile gates.
- Simple operation and user-friendly, requiring minimal training.
- Can be tailored to specific design and security requirements.
- Compact design requires less space for installation and operation.
- Easy to maintain and repair, reducing maintenance costs.
- Provides secure access control and reduces unauthorized entry.



Technical Specifications

Dimension	380*260*980
Material	304 original brushed stainless steel, acrylic
Channel Width	510mm
Thickness	The full thickness of the outer box is 1.0 + 1.2mm
Traffic Direction	One-way traffic/two-way traffic
Traffic Speed	25~30 people/min in normally open mode and 15~20 people/min in normally closed mode; The actual traffic speed is different from the traffic environment and personnel
Opening Mode	ID & IC card swiping and other reading head verification opening, button opening, etc
Opening Signal	Dry contact signal
Life	≥5 million times
Power	30-60W
Applicable Temperature	-20~75°C (add thermostat below this temperature)
Type	Bridge Type



Disclaimer: Brief product specifications are mentioned, that may change without prior notice, please check with OEM before purchase. Images are shown for reference only; the actual product may differ due to product enhancement.