



The Original Product may vary from these images

Features

- Double lane 3-rod Full Height Turnstile with a DC brushless motor.
- Operating modes: bi-direction, single-direction, always free, always locked.
- Heavy gauge materials meeting ASTM standard.
- Dual lane operation for independent to/from movements.
- Easy to integrate with existing system
- Ensures long service life.

FULL HEIGHT TURNSTILES

Model - NS-TS1-V25FDDO

Overview

It is a robust double lane 3-rod Full Height Turnstile powered by a DC brushless motor. It offers various operating modes, including bi-directional, single-directional, always free, and always locked.

Equipped with an LED directions indicator, it automatically opens or closes when powered off. It has got rugged stainless steel construction, ensuring long lasting durability.

Benefits

- Restricts unauthorized access and improves safety.
- Enables smooth flow of people and prevents overcrowding.
- Designed to withstand heavy usage and external forces.
- Can be integrated with existing systems.
- Reduces waiting times and allows for quicker entry and exit.
- · Easy to use and maintain.

Technical Specifications

Protection Level	IP44
Humidity	95%
solenoid/ motor	24V DC 100%
Signal Output	12V Plus
Passage Width	<650mm
Arms	3 spokes@120° angle x10 rotating arms (standard) 4 spokes@90° angle x10 rotating arms (optional)
Frequency	50-60Hz
Electromagnetic Drive	DC
Operating Temper Range -	-25~+70 °C
Power Supply	100V~240V AC
Power Consumption	30W
Dimension	2100x1500x2310 mm
Certification	CE, FCC, ROHS
Net Weight Including	240KG
Bars	



















Disclaimer:

Brief product specifications are mentioned, that may change without prior notice, please check with OEM before purchase. Images are shown for reference only; the actual product may differ due to product enhancement.